



US011199086B2

(12) **United States Patent**
LeBlanc et al.

(10) **Patent No.:** **US 11,199,086 B2**
(45) **Date of Patent:** **Dec. 14, 2021**

(54) **DETECTING CHANGES IN AN ENVIRONMENTAL CONDITION ALONG A WELLBORE**

(71) Applicant: **Halliburton Energy Services, Inc.**,
Houston, TX (US)

(72) Inventors: **Michel Joseph LeBlanc**, Houston, TX (US); **Wolfgang Hartmut Nitsche**, Humble, TX (US); **Jose R. Sierra**, Mexico City (MX); **Yenny Natali Martinez**, Houston, TX (US); **John Laureto Maida**, Houston, TX (US); **David Andrew Barfoot**, Houston, TX (US)

(73) Assignee: **Halliburton Energy Services, Inc.**,
Houston, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 410 days.

(21) Appl. No.: **16/305,493**

(22) PCT Filed: **Sep. 2, 2016**

(86) PCT No.: **PCT/US2016/050076**

§ 371 (c)(1),

(2) Date: **Nov. 29, 2018**

(87) PCT Pub. No.: **WO2018/044317**

PCT Pub. Date: **Mar. 8, 2018**

(65) **Prior Publication Data**

US 2021/0231006 A1 Jul. 29, 2021

(51) **Int. Cl.**
E21B 47/113 (2012.01)
E21B 47/07 (2012.01)
E21B 47/135 (2012.01)

(52) **U.S. Cl.**
CPC **E21B 47/113** (2020.05); **E21B 47/07** (2020.05); **E21B 47/135** (2020.05)

(58) **Field of Classification Search**

CPC E21B 47/00; E21B 47/04; E21B 47/06;
E21B 47/07; E21B 47/113; E21B 47/114;
E21B 47/135; E21B 2200/22

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,499,151 B2 3/2009 Bao et al.

7,599,047 B2 10/2009 Zou et al.

(Continued)

FOREIGN PATENT DOCUMENTS

WO WO 1999/045235 A1 9/1999

WO WO 2009/158630 A1 12/2009

(Continued)

OTHER PUBLICATIONS

International Search Report and the Written Opinion of the International Search Authority, or the Declaration, dated May 29, 2017, PCT/US2016/050076, 10 pages, ISA/KR.

Koyamada et al. "Fiber-Optic Distributed Strain and Temperature Sensing with Very High Measurand Resolution Over Long Range Using Coherent OTDR." *Journal of Lightwave Technology*, vol. 27, No. 9, pp. 1142-1146, May 2009.

(Continued)


Primary Examiner — Tara Schimpf

(74) Attorney, Agent, or Firm — Haynes and Boone, LLP

(57) **ABSTRACT**

A method and system can include positioning an optical waveguide along a wellbore, and launching one or more optical signals into the waveguide at one or more optical signal frequencies and during one or more time periods, thereby resulting in one or more backscattered signals being received by the receiver, which produces a trace for each of the one or more backscattered signals. Changing an environmental condition in the wellbore, generating additional backscattered light signals at one or more frequencies after the change. Comparing the traces generated before the condition change to those generated after the change, identifying a before trace and an after trace that are substantially equal to each other and identifying a frequency difference between these traces. The frequency difference can be used

(Continued)



to determine the amount of change in the environmental condition that occurred when the environmental change event happened.

20 Claims, 12 Drawing Sheets

(56)

References Cited

U.S. PATENT DOCUMENTS

8,144,314 B2 *	3/2012	Yamamoto	G01M 11/088 356/73.1
8,520,195 B2	8/2013	Ramos et al.	
9,170,149 B2	10/2015	Hartog et al.	
2005/0274513 A1	12/2005	Schultz et al.	
2007/0165691 A1	7/2007	Taverner et al.	
2008/0130707 A1 *	6/2008	Yamamoto	G01K 11/32 374/131
2011/0090496 A1 *	4/2011	Samson	E21B 47/07 356/301
2013/0257435 A1	10/2013	Smithson	
2015/0146759 A1 *	5/2015	Johnston	E21B 47/14 374/117

FOREIGN PATENT DOCUMENTS

WO	WO 2015/076976 A1	5/2015
WO	WO 2016/007161 A1	1/2016
WO	WO 2016/028288 A1	2/2016

OTHER PUBLICATIONS

Lee et al. "Optical Single Sideband Signal Generation Using Phase Modulation of Semiconductor Optical Amplifier." *IEICE Photonics Technology Letters*. vol. 16, No. 5. pp. 1373-1375. May 2004.

Loranger et al. "Rayleigh Scatter Based Order of Magnitude Increase in Distributed Temperature and Strain Sensing by Simple UV Exposure of Optical Fibre." *Scientific Reports*. vol. 5. Jun. 2015.

Lu et al. "MilliKelvin Resolution in Cryogenic Temperature Distributed Fibre Sensing Based on Coherent Rayleigh Scattering." *Proc. SPIE 23rd International Conference on Optical Fibre Sensors*. vol. 9157.

OzOptics 2012: Fiber Optic Distributed Strain and Temperature Sensors. http://www.amstechnologies.com/fileadmin/amsmedia/downloads/4549_oz_optics_fo_dstssensor.pdf.

OzOptics 2016: Fiber Optic Distributed Strain and Temperature Sensors. http://www.ozoptics.com/allnew_pdf/dts0115.pdf.

Sang et al. "One Centimeter Spatial Resolution Temperature Measurements in a Nuclear Reactor Using Rayleigh Scatter in Optical Fiber." *IEEE Sensors Journal*. vol. 8, Issue No. 7. Jul. 2008.

Imahama et al. "Restorability of Rayleigh Backscatter Traces Measured by coherent OTDR with Precisely Frequency-Controlled Light Source." *IEICE Trans. Commun.* vol. E91-B. No. 4. pp. 1243-1246. Apr. 2008.

Koyamada et al. "Novel Fiber-Optic Distributed Strain and Temperature Sensor with Very High Resolution." *IEICE Trans. Commun.* vol. E89-B. No. 5. pp. 1722-1725. May 2006.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5





FIG. 6



$A_0(f_{m,n}), \quad A_2(f_{m,n}), \quad A_4(f_{m,n}),$

FIG. 7A




FIG. 7B




FIG. 8




FIG. 9






FIG. 11



1

DETECTING CHANGES IN AN ENVIRONMENTAL CONDITION ALONG A WELLBORE

PRIORITY

The present application is a U.S. National Stage patent application of International Patent Application No. PCT/US2016/050076, filed on Sep. 2, 2016, the benefit of which is claimed and the disclosure of which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

The present disclosure generally relates to oilfield equipment and, in particular, to downhole tools, drilling and related systems, and techniques for determining a change in an environmental condition in a wellbore. More particularly still, the present disclosure relates to systems and methods for calculating the change in the environmental condition in the wellbore based on a change in an optical frequency from a frequency of a trace measured before the change to a frequency of a trace measured after the change, where the environmental condition can be at least one of temperature, pressure, and strain.

BACKGROUND

The Joule-Thomson effect causes temperature of a fluid (e.g. a gas or liquid) to change if it is pushed through a throttle, orifice, choke, or similar device, while preventing heat exchange between the fluid and the environment (that is, via an adiabatic process). The strength of the Joule-Thomson effect may depend on the particular fluid, its phase or phases, its composition (for solutions and mixtures), pressure and temperature. The effect is characterized by a coefficient called the Joule-Thomson coefficient and both the sign and magnitude of this coefficient vary with pressure, temperature, and composition of the fluid. In the case of gases in typical ambient conditions a significant cooling occurs when the gas undergoes a pressure change, such as in most refrigerators and air-conditioning systems. In the case of liquids that undergo a pressure change, the Joule-Thomson effect can be much weaker, which can result in a much smaller change in a temperature of the liquid.

Because pressure changes in a gas, when compared to a liquid, may cause more significant temperature changes, these changes can be detected and monitored by systems such as a Distributed Temperature Sensing (DTS) system, which can use Rayleigh, Raman, and/or Brillouin backscattering techniques with an optical waveguide positioned in a wellbore to measure environmental conditions (such as temperature, etc.) in the wellbore. However, the change in temperature for liquids due to a pressure change, flow rate, etc. is not readily detected using the DTS systems because the changes in temperature can be below the resolution of these DTS systems.

Therefore, it will be readily appreciated that improvements in the arts of determining changes in environmental conditions in a wellbore are continually needed.

BRIEF DESCRIPTION OF THE DRAWINGS

Various embodiments of the present disclosure will be understood more fully from the detailed description given below and from the accompanying drawings of various embodiments of the disclosure. In the drawings, like refer-

2

ence numbers may indicate identical or functionally similar elements. Embodiments are described in detail hereinafter with reference to the accompanying figures, in which:

FIG. 1 is a representative partial cross-sectional view of a marine-based well system with a system that can detect changes in environmental conditions in the wellbore according to an embodiment;

FIG. 2 is a representative partial cross-sectional view of a portion of a land-based well system utilizing the environmental condition detection system with an optical waveguide positioned in the wellbore;

FIG. 3A is a representative block diagram of a Coherent Optical Time Domain Reflectometry (C-OTDR) device which can be coupled to an optical waveguide positioned along a wellbore in the well system;

FIG. 3B is a representative block diagram of a device which can be coupled to an optical waveguide positioned along a wellbore in the well system;

FIG. 4 illustrates a representative C-OTDR trace “t1” for the portion of the optical waveguide in the steady-state environment taken at an initial optical signal frequency and a representative C-OTDR trace “t2” for the portion of the optical waveguide at a changed environmental condition from the steady-state environment taken at the initial optical signal frequency.

FIG. 5 illustrates the representative C-OTDR trace “t1” for the portion of the optical waveguide in the steady-state environment taken at the initial optical signal frequency and a representative C-OTDR trace “t3” for the portion of the optical waveguide at a changed temperature taken at a changed optical signal frequency.

FIG. 6 illustrates a representative block diagram of a method for detecting changes in an environmental condition in the wellbore.

FIG. 7A illustrates a plot of traces collected over time to track large changes in temperature.

FIG. 7B illustrates a representative block diagram of a method for detecting large changes in an environmental condition in the wellbore.

FIG. 8 illustrates a representative 2-axis shade level plot of a correlation value “Corr” and an array of compared traces which are collected at a range of initial and changed optical frequencies, as well as a line through high correlation values of the compared traces.

FIG. 9 illustrates a representative plot of an initial backscattered light signal collected at an initial frequency at initial environmental conditions during a first time period.

FIG. 10A illustrates a representative plot of a backscattered light signal collected at an initial frequency with changed environmental conditions during a second time period.

FIG. 10B illustrates a representative plot of a backscattered light signal collected at a second frequency with changed environmental conditions during the second time period.

FIG. 11 illustrates a representative plot of correlation values for backscattered signals at frequencies from 4.4 GHz to 4.6 GHz.

DETAILED DESCRIPTION OF THE DISCLOSURE

The disclosure may repeat reference numerals and/or letters in the various examples or Figures. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship between the various embodiments and/or configurations discussed. Further, spatially relative

terms, such as beneath, below, lower, above, upper, uphole, downhole, upstream, downstream, and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated, the upward direction being toward the top of the corresponding figure and the downward direction being toward the bottom of the corresponding figure, the uphole direction being toward the surface of the wellbore, the downhole direction being toward the toe of the wellbore. Unless otherwise stated, the spatially relative terms are intended to encompass different orientations of the apparatus in use or operation in addition to the orientation depicted in the Figures. For example, if an apparatus in the Figures is turned over, elements described as being "below" or "beneath" other elements or features would then be oriented "above" the other elements or features. Thus, the exemplary term "below" can encompass both an orientation of above and below. The apparatus may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein may likewise be interpreted accordingly.

Moreover even though a Figure may depict a horizontal wellbore or a vertical wellbore, unless indicated otherwise, it should be understood by those skilled in the art that the apparatus according to the present disclosure is equally well suited for use in wellbores having other orientations including vertical wellbores, slanted wellbores, multilateral wellbores or the like. Likewise, unless otherwise noted, even though a Figure may depict an offshore operation, it should be understood by those skilled in the art that the method and/or system according to the present disclosure is equally well suited for use in onshore operations and vice-versa. Further, unless otherwise noted, even though a Figure may depict a cased hole, it should be understood by those skilled in the art that the method and/or system according to the present disclosure is equally well suited for use in open hole operations.

As used herein, the words "comprise," "have," "include," and all grammatical variations thereof are each intended to have an open, non-limiting meaning that does not exclude additional elements or steps. While compositions and methods are described in terms of "comprising," "containing," or "including" various components or steps, the compositions and methods also can "consist essentially of" or "consist of" the various components and steps. It should also be understood that, as used herein, "first," "second," and "third," are assigned arbitrarily and are merely intended to differentiate between two or more objects, etc., as the case may be, and does not indicate any sequence. Furthermore, it is to be understood that the mere use of the word "first" does not require that there be any "second," and the mere use of the word "second" does not require that there be any "first" or "third," etc.

The terms in the claims have their plain, ordinary meaning unless otherwise explicitly and clearly defined by the patentee. Moreover, the indefinite articles "a" or "an," as used in the claims, are defined herein to mean one or more than one of the element that it introduces. If there is any conflict in the usages of a word or term in this specification and one or more patent(s) or other documents that may be incorporated herein by reference, the definitions that are consistent with this specification should be adopted.

Generally, this disclosure provides a method and system to detect small changes in downhole environmental conditions in a wellbore. For example, temperature changes on the order of 1 to 10 mK (millikelvin) and small strain changes can be detected. The system can include an optical wave-

guide, a precision frequency optical light source coupled to the waveguide, and an optical receiver coupled to the waveguide. The optical light source can produce an optical signal at a substantially constant frequency which can then be externally tuned using optical modulation techniques to precisely control the optical frequency of the light. The optical waveguide can be installed in a wellbore on a conveyance vehicle (e.g. tubing strings, slickline, wireline, etc.). The method and system of this disclosure can detect small changes in downhole environmental conditions because the optical waveguide's properties are sensitive to changes in the environmental conditions. The optical light source can be coupled to the waveguide for launching light at a substantially constant frequency into the waveguide and the optical receiver can be coupled to the waveguide to receive backscattered light from the waveguide. Because of the response of the waveguide's properties to environmental changes, the backscattered light contains information about how the waveguide's properties were modified by the environment. Therefore, this backscattered light can be used to create one or more measurement traces that represent(s) a profile of an environmental condition along at least a portion of a length of the wellbore. The measurement trace(s) can be created by interference between backscattered light from different inherent scatterers within the waveguide.

When an environmental condition changes, the frequency of the optical light source can be adjusted to compensate for the change in the environmental condition. In other words, the measurement trace obtained when the waveguide "is not" subject to a given environmental condition can be recuperated by using light at a different frequency when the waveguide "is" subject to the given environmental condition. The frequency shift that compensates for the environmental condition change can be determined when a measurement trace at the adjusted frequency substantially correlates with a measurement trace obtained prior to the change of the environmental condition. When the measurement traces, which are taken before and after the environmental change, substantially match each other (i.e. have a high correlation value from 0.8-1.0), then the change in the environmental condition can be determined based on the difference between the optical frequencies used to produce the before and after traces. Furthermore, by determining the change in the environmental condition, other aspects of the fluid flowing in the wellbore may also be determined, such as fluid type, fluid composition, fluid flow rate, pressure drop between the formation and the wellbore, watercut, location(s) of production zone(s) in the wellbore, etc.

It should be understood that the optical waveguide, light source, and backscattered light receiver of this disclosure can also be used to perform additional tasks such as detecting temperature profiles via a Distributed Temperature Sensing (DTS) system using backscattering techniques (e.g. Raman, Rayleigh, and/or Brillouin), detecting absolute pressure measurements downhole, detecting acoustic signals via Distributed Acoustic Sensing (DAS), transmitting command and control data to/from downhole equipment, transmitting collected sensor data and/or telemetry data to/from downhole equipment, etc. These tasks can be performed along with the method and system of the current disclosure.

Turning to FIG. 1, this figure shows an elevation view in partial cross-section of a wellbore production system 10 which can be utilized to produce hydrocarbons from wellbore 12. Wellbore 12 can extend through various earth strata in an earth formation 14 located below the earth's surface 16. Production system 10 can include a rig (or derrick) 18. The rig 18 can include a hoisting apparatus, a travel block,

5

and a swivel (not shown) for raising and lowering casing, or other types of conveyance vehicles **30** such as drill pipe, coiled tubing, production tubing, and other types of pipe or tubing strings, such as wireline, slickline, and the like. In FIG. 1, the conveyance vehicle **30** is a substantially tubular, axially extending work string or production tubing, formed of a plurality of pipe joints coupled together end-to-end supporting a completion assembly as described below. However, it should be understood that the conveyance vehicle **30** can be any of the other suitable conveyance vehicles, such as those mentioned above. The conveyance vehicle **30** can include one or more packers **20** to prevent (or at least restrict) flow of production fluid through an annulus **32**. However, packers **20** are not required.

The wellbore production system **10** in FIG. 1 is shown as an offshore system. A rig **18** may be mounted on an oil or gas platform, such as the offshore platform **44** as illustrated, and/or semi-submersibles, drill ships, and the like (not shown). One or more subsea conduits or risers **46** can extend from platform **44** to a subsea wellhead **40**. The tubing string **30** can extend down from rig **18**, through subsea conduits **46**, through the wellhead **40**, and into wellbore **12**. However, the wellbore production system **10** can be an onshore wellbore system, in which case the conduits **46** may not be necessary.

Wellbore **12** may be formed of single or multiple bores, extending into the formation **14**, and disposed in any orientation (e.g. vertical, inclined, horizontal, combinations of these, etc.). The wellbore production system **10** can also include multiple wellbores **12** with each wellbore **12** having single or multiple bores. The rig **18** may be spaced apart from a wellhead **40**, as shown in FIG. 1, or proximate the wellhead **40**, as can be the case for an onshore arrangement. One or more pressure control devices (such as a valve **42**), blowout preventers (BOPs), and other equipment associated with drilling or producing a wellbore can also be provided in the system **10**. The valve **42** can be a rotating control device proximate the rig **18**. Alternatively, or in addition to, the valve **42** can be integrated in the tubing string **30** to control fluid flow into the tubing string **30** from an annulus **32**, and/or controlling fluid flow through the tubing string **30** from upstream well screens.

An optical light source/receiver device **52** can be coupled to an optical waveguide **50** installed along the tubing string **30** in the wellbore **12**. The optical light source/receiver **52** can be a device known as a Coherent-Optical Time Domain Reflectometry (C-OTDR) device, a Coherent-Optical Frequency Domain Reflectometry (C-OFDR) device, or any other suitable device for launching light into the optical waveguide at a substantially constant frequency and receiving backscattered light from the waveguide (e.g. Rayleigh backscattering). As used herein, the terms "substantially constant frequency" and "stable frequency" refer to a frequency of the optical light source **122** that may vary up to ± 10 MHz long term. Frequencies that remain within this tolerance are seen as being "substantially constant" and/or "stable." A representative block diagram of a device **52** is shown in FIGS. 3A and 3B. It should be understood that the device **52** can include more or fewer components than the components shown in FIG. 3A or 3B. These components can be incorporated into a single chassis, or one or more of these components can be housed in one or more separate chassis and coupled together to perform the functions of the device **52**. The device **52** can provide an optical pulsed signal **54** at a settable stable frequency which is coupled to the optical waveguide **50**. As the optical signal **54** travels through the optical waveguide **50**, backscattered light **56** is returned to the device **52**, which detects the received backscattered

6

light, records an intensity of the backscattered light **56** vs. time, and creates a trace that represents the intensity of the backscattered light **56** received from points along a length of the optical fiber **50** and therefore, along a length of the wellbore **12**.

The optical waveguide **50** is shown in FIG. 1 extending through the annulus **32** along the tubing string **30**, and past production zones **60**, **62**, **64**. It should be understood that the optical waveguide is not required to be positioned in the annulus **32**. It can be otherwise positioned, such as within the tubing string **30**, attached to a casing string **34**, and deployed in the wellbore via various other conveyance vehicles (e.g. coiled tubing, wireline, slickline, etc.). FIG. 1 also shows three production zones **60**, **62**, **64**, but any number of production zones can be supported by the method and system of this disclosure. If a location of the production zones **60**, **62**, **64** along the wellbore is unknown, then the location(s) can be determined by sensing a change in an environmental condition (such as temperature, pressure, etc.) in the fluid when the fluid flows (or is prevented from flowing) from the formation **14** into the wellbore **12**. If the location along the wellbore of each production zone **60**, **62**, **64** is known (e.g. a wellbore with known locations of perforations **36** created at each of the production zones **60**, **62**, **64**), then a portion of the length of the wellbore **12** to be evaluated can be localized to the known perforation zones, and evaluation times can be minimized. However, it is not required that the evaluation times be minimized.

FIG. 2 shows the production system **10** as a land-based (onshore) system **10**, with the rig **18** and tubing string **30** not shown for clarity. The wellbore **12** has penetrated the earth formation **14** and has a horizontal portion. Perforations **36** have been created at each of the production zones **60**, **62**, **64**. The production zones **60**, **62**, **64** can be located within a single producing zone, and/or located within separate producing zones of the formation **14**. Fluids **70**, **72**, **74** can flow from respective production zones **60**, **62**, **64** into the wellbore **12** via the perforations **36**. The fluid **74** can come in the wellbore **12** with the fluid **72**, and the mixture of fluids **72**, **74** can come in the wellbore **12** with the fluid **70** to produce the fluid **76** which can be produced through the wellbore **12** to the surface through valve **42**. The fluids **70**, **72**, **74**, **76** can be liquid, gas, a composition of various liquids, a composition of various gases, combinations of these, etc. When the valve **42** is closed, flow from the production zones **60**, **62**, **64** can be prevented (or at least significantly restricted), thereby causing pressures **P1**, **P2**, **P3**, **P4** to equalize. If some pressure variations are present between the pressures **P2**, **P3**, **P4**, then some fluid may flow between the production zones, but it is preferable that fluid flow between production zones is minimized. With flow through the wellbore prevented (or minimized), a profile of the environmental condition along the wellbore can stabilize to a steady state condition. It should be understood that the valve **42** can be positioned at an end of a tubing string **30** and positioned further downhole than the production zones **60**, **62**, **64**. If a production tubing string **30** is used in the wellbore as shown in FIG. 1, the fluids **70**, **72**, **74** flowing into the wellbore **12** from the formation **14** can initially flow further downhole, before flowing through the valve **42** as fluid **76** and into the production tubing string **30**, which can carry the fluid **76** to the surface or to any other desired location. Therefore, fluid **70** can flow downhole to come in with fluid **72** in the annulus **32**, and the resulting fluid mixture can flow further downhole to come in with fluid **74**

in the annulus, which can result in the fluid **76** (which can be a single fluid type or a composition of fluid types) flowing in the annulus **32**.

The device **52** and optical waveguide **50** can be used to collect baseline traces at one or more optical signal frequencies. The device **52** can launch an optical light signal **54** at a substantially constant frequency into the waveguide and receive a backscattered light signal **56** from the waveguide **50** (e.g. using Rayleigh backscattering). The device **52** can produce a trace that represents an intensity of the backscattered light signal **56** along a distance of the waveguide **50**. One of more baseline traces can be produced that are representative of an environmental condition (e.g. temperature, pressure, strain, etc.) in the wellbore **12** at one or more of the locations of the production zones **60**, **62**, **64**, and/or other locations along the wellbore. The device **52** can be a C-OTDR device.

FIG. **3A** shows a representative block diagram of the device **52** that can be used to launch an optical signal **54** into the waveguide **50** and receive a backscattered signal **56** from the waveguide **50**. For this configuration of the device **52**, a simple frequency stabilized laser diode **122** is used to supply an optical signal at a stable frequency to a single side band (SSB) modulator **130**. The frequency of the light source **122** can be adjusted by controlling a frequency shift at the SSB modulator **130**. An example of commercial SSB modulator is the ModBox-CS-SSB-1550 from Photline Technologies (Besancon, France). The SSB modulator **130** sends the adjusted optical signal to the pulse generator **126** which creates a pulsed optical signal **54** that is launched into the waveguide **50** through a circulator **128**. A backscattered light signal **56** is returned to the device **52** in response to the backscattering of the optical signal **54** by the optical waveguide. This backscattered light signal **56** can be received by the photo detector **146**, and the device **52** can create a trace that represents the intensity of backscattered light along the waveguide **50**. Instead of circulator **128**, a fiber optic coupler (e.g., 3 dB directional coupler) can also be used. The device **52** can produce a trace that is a time resolved intensity of Rayleigh backscattering. The time delay after which a backscattered light is measured can correspond to a position in the fiber at which the backscattering occurred (due to the constant speed of light). The pattern of the backscattered light signal **56** can stay substantially the same over extended periods of time (hours to days or longer), if the environment in the wellbore remains constant. The backscattered light signal **56** can be very sensitive to variations in environmental conditions (such as temperature, pressure, strain, etc.) in the wellbore.

FIG. **3B** shows another representative block diagram of components that can be used in a device **52**. The C-OTDR device **52** can include a controller (or computer) **120** that controls the other components, transfers data to/from other components, receives inputs from an operator, and transmits results to the operator. An analog-to-digital converter **138** can interface the digitally based computer to a balanced photo-electric diode **146**. Circulator **128** and couplers **140**, **148** can route optical signals within the device **52**. For example, coupler **148** can connect the optical signal from a light source **122** (e.g. a laser diode) to the balanced photo-electric diode **146**. In this example, the light source **122** is a frequency stabilized distributed feedback laser diode (DFB-LD) emitting at optical frequency ν_0 . However, it should be understood, that this is only one possible laser source that can be used in keeping with the principles of this disclosure. Any suitable frequency stabilized laser source that provides a stable optical frequency can be utilized. The frequency of

the output of the light source **122** can be precisely shifted by passing the output of the light source **122** into a single side band modulator (SSB) **130** that can be driven by a microwave synthesizer **124** (e.g., high speed function generator). The frequency of the light source **122** can be adjusted by controlling the frequency shift $\Delta\nu_{SSB}$ at the SSB modulator **130** to produce light at a new optical frequency $\nu = \nu_{laser} + \Delta\nu_{SSB}$. The resulting optical signal can be divided (via coupler **140**) into two signals. One signal can be routed to the balanced photo diode **146** as a local oscillator signal, and the other signal can be passed through an electro-optic modulator (EOM) **132** and an acoustic optic modulator (AOM) **134** which can both be driven by a pulse generator **126**. The output of the EOM **132** and AOM **134** components can provide a pulsed optical signal **54**.

Polarization controllers **142**, **144** can be used to optimize the signal strength at the balanced photo detector **146**. The pulsed optical signal **54** can then be amplified (e.g. by an erbium-doped fiber amplifier (EDFA)) and launched into the waveguide **50**. As a backscattered light signal **56** is received from the waveguide **50**, the signal **56** can be combined at the coupler **148** with the local oscillator signal from the coupler **140** and then detected by the balanced photo diode (PD) receiver **146**. The controller **120** can receive a digitized version of the detected signal and produce a representative trace of the signal **56** and transmit the trace to an operator, where the trace can represent the intensity of the backscattered light along at least a portion of the wellbore **12**. The C-OTDR device **52** can also produce a trace that is a time resolved intensity of Rayleigh backscattering. Therefore, it is seen that several configurations of the device **52** can be used to support the principles of this disclosure.

FIG. **4** illustrates the sensitivity of the backscattered light signal **56** to small changes in temperature, with other environmental conditions in a steady-state. (Temperature is used here as an example of a changing environmental parameter, but it should be understood that other physical parameters of interest can be monitored instead, such as pressure, or strain.) In this example, two traces **90**, **94** have been produced in response to receiving two separate backscattered signals **56** from the waveguide **50** at two separate time periods. The trace **90** was collected initially at a first time period with the environment around the optical waveguide at about 303 degrees Kelvin, and with a SSB frequency shift ($\Delta\nu_{SSB}$) of the optical signal at 4.39 GHz. The trace **94** was collected a minute later at the same optical signal frequency, but at a slightly changed temperature. [Note: Because the optical frequency is adjusted by the change in the SSB modulation frequency, different values of SSB frequency correspond to different optical frequencies. For this reason, when it is desirable to indicate two different optical frequencies, two different values of SSB frequencies ($\Delta\nu_{SSB}$) are quoted because, in practice, this is what can be changed to achieve the difference in optical frequency.] A temperature probe was used to monitor the environmental temperature around the waveguide **50** and the probe's measurements determined that the temperature had dropped 28 mK. As can be seen from FIG. **4**, the two traces **90**, **94** are quite dissimilar indicating the sensitivity of backscattered light to very small changes in temperature. As will be discussed in more detail below, this change in an environmental condition (e.g. temperature in this example) can be compensated for by adjusting the optical signal frequency to produce a new trace that is substantially the same as the initial trace **90** (e.g. trace **96** in FIG. **5**). When the before and after traces **90**, **96** are substantially equal (to be defined in detail below in terms of cross-correlation value), the amount of frequency

adjustment needed to produce a substantially equal trace **96** can be used to calculate (or determine) the change in the environmental condition.

If the environmental absolute temperature T is close to some initial temperature T_0 ; then this means that $T=T_0+\Delta T$ with $\Delta T \ll T_0$, where ΔT is a change in temperature from the initial temperature T_0 to the new temperature T . Similarly, if the optical signal frequency ν of the laser light is close to some initial frequency ν_0 ($=\nu_{laser}+\Delta\nu_{SSB_0}$), then this means $\nu=\nu_0+\Delta\nu$ with $\Delta\nu \ll \nu_0$, where $\Delta\nu$ is the change in frequency from the initial frequency ν_0 to the final frequency ν .

A correlation value $Corr$, can be used to indicate a correlation between two separate traces. If $A_1(n)$ is the first trace and $A_2(n)$ is the second trace (with n being the index for a specific data point, for example $n=1 \dots 10000$ if a total of $N=10000$ data points are measured), then the correlation between the two traces can be defined by equation (1),

$$Corr = \frac{1}{N} \sum_{n=1}^N \frac{A_1(n) - \mu_{A_1}}{\sigma_{A_1}} \times \frac{A_2(n) - \mu_{A_2}}{\sigma_{A_2}} \quad (1)$$

where

$$\mu_{A_1} = \frac{1}{N} \sum_{n=1}^N A_1(n)$$

is the mean of $A_1(n)$, and

$$\sigma_{A_1} = \sqrt{\frac{1}{N} \sum_{n=1}^N (A_1(n) - \mu_{A_1})^2}$$

is its standard deviation, and likewise for μ_{A_2} and σ_{A_2} . If the correlation value $Corr$ equals "1" (one), the two signals are seen to be identical to each other (or the highest correlation). If the correlation value $Corr$ equals "0" (zero), then the two signals are seen to have nothing in common (or minimal correlation). Correlation values $Corr$ that have a magnitude between "1" and "0" indicate that the two signals at least partially correlate to each other, with values closer to "1" indicating a higher correlation and values closer to "0" indicating a lower correlation.

In an approximation, for the case of the environmental perturbation affecting only temperature, the trace can depend only on a distance d and a quantity δ , where

$$\delta = \Delta T + 0.75 \frac{mK}{MHz} \Delta \nu.$$

Therefore, this indicates that if the temperature changes, the frequency can be fine-tuned afterwards until the quantity δ becomes zero in which case the trace can be substantially equal to the initial trace. In the case where the first and second traces $A_1(n)$, $A_2(n)$ have a correlation value that is close to "1," then the first and second traces may be seen as being substantially equal to each other. As used herein, a correlation value "Corr" that is greater than or equal to 0.80 indicates that the correlation is "close to 1" and that the two traces being correlated are substantially equal to each other.

With the indication from the correlation value $Corr$ that the two traces are substantially equal to each other, then the quantity δ may be assumed to be zero and the change in temperature can be determined from the frequency change in by solving for ΔT , which results in equation (2):

$$\Delta T = -0.75 \frac{mK}{MHz} \Delta \nu \quad (2)$$

Therefore, the change in temperature can be calculated based on the change in frequency used to cause the second trace to have a correlation value in the range of 0.8 to 1.0 with the first trace. This example assumes that a strain on the fiber is substantially constant and does not change significantly during the determination of the change in temperature. Therefore, the portion of the change in frequency necessary to compensate for any change in strain of the optical waveguide is considered to be negligible for the purposes of calculating the change in temperature based on the change in frequency between the first and second traces. It should be noted, that the before and after traces refer to two traces that have a correlation $Corr$ from 0.8 and 1.0. A plurality of traces can be collected at the initial and final environmental conditions, with each of the traces collected at the initial conditions correlated to each of the traces collected at the final conditions, thereby providing many independent measurements of the desired frequency shift.

In the example above, traces **90**, **94**, a temperature shift of -28 mK caused a noticeable difference between the trace **90** produced prior to the temperature change during time period **t1**, and the trace **94** produced after the temperature change during time period **t2**. As per the discussion above, the frequency of the optical signal launched into the optical waveguide **50** from the device **52** can be fine-tuned to compensate for the change in the environmental temperature. FIG. 5 shows the trace **90** and a third trace **96**, with the trace **96** being taken at a third time period **t3**, which was after the temperature shift of -28 mK, and with the optical signal frequency adjusted to 4.39 GHz ($\Delta\nu=39$ MHz). The two traces **90**, **96** are substantially equal to each other, which indicate that the change in frequency has substantially compensated for the change in the environmental temperature. (This can also be illustrated by calculating the correlation $Corr$ between the traces **90**, **96** using equation (1) above.)

Therefore, the change in frequency can be used to calculate the change in the environmental temperature. Accordingly, equation (2) shows a calculation for ΔT based on the change in frequency. As equation (3) shows, the change in frequency of 39 MHz results in a calculated temperature change of 29 mK, which very closely approximates the actual temperature change of -28 mK measured by the temperature probe in this example.

$$\Delta T = 0.75 \frac{mK}{MHz} * 39 \text{ MHz} = 29 \text{ mK} \approx -28 \text{ mK} \quad (3)$$

By making similar measurements with the waveguide **50** positioned in a wellbore **12**, a change in temperature in a liquid at each of the production zones **60**, **62**, **64**, can be calculated by determining the change in frequency of the optical signal that respectively compensates for the amount

11

of change in the environmental temperature at each of the production zones **60**, **62**, **64** as fluid flows from the formation **14** into the wellbore **12**.

A change in strain of the fiber can be similarly calculated from a change in frequency, assuming the temperature remains constant during the measurements to determine the strain change. Much like the process for determining a change in temperature, the change in strain can have a linear relationship with the change in frequency of the optical signal **54** which is launched into the waveguide **50**. The change in the strain can be calculated when two traces taken at different optical signal frequencies (one taken before the strain change and one taken after the strain change) have a correlation value Corr between 0.8 to 1.0. The difference in the optical signal frequencies can be used to calculate the change in the strain. The laser frequency change $\Delta\nu$ that compensates for the strain change $\Delta\varepsilon$ is given by equation (4):

$$\frac{\Delta\nu}{\nu_0} \approx -0.78 \times \Delta\varepsilon \quad (4)$$

Solving for $\Delta\varepsilon$ yields equation (5):

$$\Delta\varepsilon \approx -1.28 \times \frac{\Delta\nu}{\nu_0} \quad (5)$$

FIG. 6 shows a representative block diagram for a method **200** which can be used to detect changes in an environmental condition(s) (e.g. temperature, pressure, strain, etc.) along a wellbore. The method **200** can include the steps **202-220** as shown, but the method **200** can also include more or fewer steps than those shown in FIG. 6. In step **202**, an optical waveguide **50** can be positioned along a wellbore **12** via one of various conveyance vehicles **30** as given above. A light source **122** (which can be included in the device **52**, see FIGS. 3A, 3B) can be coupled to the optical waveguide **50** in step **204** and can introduce (or launch) an optical signal **54** at a first frequency into the waveguide **50** during a first time period. The first time period can be the amount of time needed for the optical signal **54** to travel through the waveguide **50** to reach a desired location(s) in the wellbore **12** and for the backscattered light signal **56** to be received by the device **52**. Preferably, the desired location or locations are at least one of the productions zones **60**, **62**, **64**. However, the desired location can be any location along the wellbore **12**.

In step **206**, a backscattered signal **56** can be received from the optical waveguide **50** in response to the introduction of the optical signal **54** during the first time period. A first trace can be produced that represents an intensity of the backscattered light along the waveguide **50** during the first time period. This first trace can also be seen as a baseline trace (i.e., a trace representing the initial conditions) that provides a baseline to which other traces are compared. It should also be noted that this first trace can include multiple traces at multiple different frequencies to provide a wide range of backscattered signals **56** with which to compare against future traces. It is not required that the first, initial, or baseline trace be a singular trace.

After the initial trace or traces are collected in step **206**, the environmental condition(s) can be changed in step **208**. There are many ways one or more of the environmental conditions downhole can be changed in keeping with the

12

principles of the current disclosure. For example, opening or closing a valve **42** (see FIG. 2) can selectively permit and prevent fluid flow through the wellbore **12**. By changing the fluid flow, environmental conditions (e.g. pressures, temperatures, strain, etc.) can be changed from an initial state to an altered state. The altered fluid flow can cause a change in the environmental condition by altering the Joule-Thompson effect. Operating the valve **42** can change a pressure differential between pressure **P1** in the wellbore **12** and formation pressures **P2**, **P3**, **P4** at the respective production zones **60**, **62**, **64**. Initially, the valve **42** can be open to allow a fluid **76** to flow out of the wellbore **12**, which can enable fluids **70**, **72**, **74** to flow into the wellbore from the formation **14**. In this case, the Joule-Thompson effect can cause a temperature change in each of the fluids **70**, **72**, **74** as the fluids flow out of the formation **14** and in to the wellbore **12**. With steady-state fluid flow, a profile of the environmental condition in the wellbore can reach a steady state condition. It is during this steady state condition that the initial trace(s) can be collected as in step **206**.

If the valve **42** is then partially (or fully) closed, a backpressure from the closed valve **42** can cause pressure **P1** in the wellbore to equalize with pressures **P2**, **P3**, **P4** in the formation **14** at the respective production zones **60**, **62**, **64**. Equalizing these pressures, reduces (or eliminates) the flow of the fluids **70**, **72**, **74** into the wellbore **12**. With reduced fluid flow, the Joule-Thompson effect in each of the fluids **70**, **72**, **74** is reduced (or eliminated), thereby allowing the temperatures of the fluids **70**, **72**, **74** to equalize with the temperatures of the formation **14** at the respective production zones **60**, **62**, **64**. Equalizing the temperatures (and pressures) at the production zones **60**, **62**, **64**, can cause a change in temperature of each of the fluids **70**, **72**, **74** by reduction and/or elimination of the Joule-Thompson effect in these fluids.

Alternatively, the environmental condition change can also be caused by having the valve **42** initially closed and then opening the valve **42** to permit fluid flow from the wellbore **12**. With the valve **42** initially closed, flow of fluid **76** is prevented (or significantly restricted), thereby preventing (or significantly restricting) flow of fluids **70**, **72**, **74** from the formation **14** into the wellbore **12** at the production zones **60**, **62**, **64**. Without a pressure drop between the production zones **60**, **62**, **64** and the formation **14**, the temperatures and pressures at these zones can equalize with the formation **14** temperatures and pressures to provide a stable environmental condition profile along the wellbore **12**. The initial trace(s) can be collected while the environmental conditions (e.g. temperature, pressure, strain, etc.) are stable and the valve **42** is closed. After collection of the initial trace(s), then the environmental condition can be changed by opening the valve **42**. Opening the valve **42**, can allow fluid **76** to flow through the wellbore **12**, thereby creating a pressure differential in the fluids **70**, **72**, **74** at the respective production zones **60**, **62**, **64**. The pressure differential in each of the fluids **70**, **72**, **74** can cause the temperature in the fluids to change due to the Joule-Thompson effect.

Once the environmental change has occurred, a next trace can be collected by adjusting the frequency of the light source **122** to a next frequency in step **210** that is different from the first frequency, introducing an optical signal **54** from the light source **122** into the optical waveguide **50** at the next frequency during a next time period in step **212**, and receiving a next backscattered signal **56** from the optical waveguide **50** in response to the introduction of the optical signal **54** during the next time period in step **214**. The next

13

trace, which represents an intensity of the next backscattered signal **56** along the waveguide **50** during the next time period, can be produced and transmitted to the controller **60** for analysis. The initial (or first) and next (or second) traces can be compared in step **216** to determine if there are any differences between them. This comparison can be performed by calculating the correlation value (i.e. Corr) between the initial and next traces and determining if the resulting correlation value is within an acceptable range. As given above, if the correlation value is within a range from 0.8 to 1.0, then the signals can be deemed as being substantially the same. The steps **210**, **212**, **214**, **216** can be repeated as many times as needed to produce a next (or second) trace that is substantially equal to the initial (or first) trace. In other words, the next frequency can be adjusted (step **210**), the next trace collected for the adjusted frequency (steps **212**, **214**), and the next (or second) trace compared to the first trace (step **216**) as many times as desired to produce a next trace that is substantially the same as the first trace (or at least substantially the same as one or more of the first traces). Additionally, the next trace can also include multiple traces, where, in step **216**, one of the first traces can be compared to one or more of the next traces until one or more of the first traces is deemed to be substantially equal one or more of the next traces.

When step **216** determines that at least one initial trace is substantially equal to at least one next trace, then the difference between the frequency of the substantially equal initial and next traces can be used to calculate the change in the environmental condition in step **218**, such as using equation (2) to calculate a change in temperature, and/or equation (5) above to calculate a change in strain. When the change in the environmental condition has been determined, then one or more fluid characteristics (such as fluid type, fluid composition, fluid flow, fluid pressure differential, etc.) can be determined based on the environmental condition change. For example, if temperature is the environmental condition that changed at a wellbore location during step **208**, a strain of the waveguide **50** remains substantially constant, the wellbore volumes at the location are known, and wellbore and formation pressures at the location are known, then the temperature change determined in step **218** can be used to determine an effective Joule-Thompson coefficient for the fluid flowing into the wellbore at the wellbore location. The effective Joule-Thompson coefficient can be used to determine a composition of the fluid flowing into the wellbore **12** at the location, or fluid flow rate (if fluid composition is known), etc. If an actual Joule-Thompson coefficient of the fluid composition is known, then one or more of the other characteristics (such as fluid pressure differential, fluid flow rate, change in strain, etc.) can be determined based on the difference between the frequency of the initial trace and the next trace which has sufficient correlation.

There are several approaches for collecting initial and next traces to identify a change in an environmental condition in the wellbore **12**. One example of an approach can be to measure one initial trace at a single frequency, change the flow rate, and then measure multiple traces at many different frequencies. The initial trace can then be compared to each one of the multiple traces to identify which one (or more) of the multiple traces correlate best with the initial trace. The difference in frequency between the initial trace and the one (or more) of the multiple traces, which best correlate, can be used to calculate the change in the environmental condition.

As way of another example, many initial traces at multiple different frequencies can be collected prior to a change in the

14

environmental condition, after which the environmental condition can be changed, and then one final trace at one single frequency can be measured. Each of the initial traces can be compared to the final trace to determine which one or more of the initial traces correlate with the final trace. The difference in frequency between the one or more of the initial traces and the final trace can be used to calculate the change in the environmental condition.

As way of another example, one initial trace at one single frequency can be collected prior to a change in the environmental condition, after which the environmental condition can be changed, and then new traces can be continuously collected and compared to the initial trace as the optical signal frequency is slowly changed. When the comparison between the initial trace and one or more of the new traces identifies the new traces that best correlate to the initial trace, then the frequency difference between these initial and one or more new traces can be used to calculate the change in the environmental condition.

As way of yet another example, many initial traces at multiple different frequencies can be collected prior to the change in the environmental condition, after which the environmental condition can be changed, and many final traces at many different frequencies can be collected. Each of the initial traces can be compared to each one of the final traces to determine which one or more of the initial traces best correlate with one or more of the final traces. By plotting the result as a 2D color map, or a 2D shade level map (as done in FIG. **8**), and fitting a line along the points of highest correlation, the frequency change necessary to cancel out the temperature change can be calculated and the frequency change can be used to calculate the change in the environmental condition (this example approach is explained in more detail below regarding FIG. **8**).

As way of yet another example, FIG. **7A** shows a plot that represents temperature changes that may progress over time to drift outside of a frequency span S of an instrument (i.e. device **52**) during the environmental change event. Times t_1 and t_2 represent start times for any two sets of before and after traces, with one or more before traces (i.e. traces taken before the change event) taken at time t_1 , and a first set of one or more after traces (i.e. traces taken after the change event has begun) taken at time t_2 . A frequency shift Δf can be determined, as described above, by correlation of the before and after traces to identify the pair of traces with the best correlation and using those signals to determine Δf . However, this assumes that the amount of temperature change that occurs between the start of the change event to the end of the change event does not correspond to frequency shifts beyond the capability of the device **52**. Method **300** (see FIG. **7B**) is directed to the times this assumption is not valid and the amount of temperature change that occurs between the start of the change event and the end of the change event does correspond to frequency shifts beyond the capability of the device **52**.

FIG. **7A** illustrates the evolution of temperature at point z_i over time, starting from $t=t_0$. Because of the frequency span used, a maximum correlatable temperature shift may be limited to ΔT_{max} , as shown. With $A_0(f_m, n)$ used as a set of one or more "before" traces, collected at $t=t_0$, the peak frequency shift can be determined for sets of after traces collected after the change event begins at times t_1 , t_2 and t_3 . However, without changing the frequency range of the device **52**, if a set of "after" traces $A_4(f_m, n)$ were taken at time t_4 , no correlation would be achievable with the baseline dataset $A_0(f_m, n)$. It would therefore be seemingly impossible to calculate the temperature change $\Delta T_{0 \rightarrow 4}$ between

15

times t_0 and t_4 directly by the datasets $A_0(f_m, n)$, $A_4(f_m, n)$ collected at those two times. However, a dataset $A_2(f_m, n)$ collected at an intermediate time t_2 can be correlated to dataset $A_4(f_m, n)$, thereby permitting calculation of a temperature shift $\Delta T_{2 \rightarrow 4}$ that occurred at z_i during time interval between times t_2 and t_4 . The total temperature change $\Delta T_{0 \rightarrow 4}$ that occurred between times t_0 and t_4 can be calculated by summing the temperature change $\Delta T_{0 \rightarrow 2}$ between times t_0 and t_2 and the temperature change $\Delta T_{2 \rightarrow 4}$ between times t_2 and t_4 . This process can also be similarly applied to determining changes in other environmental conditions, such as pressure and strain. (Again, please note that temperature is discussed above merely for purposes of discussion. This discussion can also similarly apply to other conditions such as pressure and strain.)

Therefore, as long as the time intervals between the datasets are short enough to ensure that an environmental condition change between two contiguous times can be correlated to determine a frequency shift, the incremental condition change between those contiguous points can be calculated and thus the overall condition change can be calculated. Because each condition increment is determined with a non-zero uncertainty, by adding up the condition increments to obtain the full condition change, a cumulative effect of the uncertainty can occur (following a standard propagation of errors for a sum of measurements). The uncertainties can be minimized by having a device 52 with a large frequency span (2 S) and that datasets be collected at certain condition increments, so as to minimize the number of steps between the current condition shift measurement and the baseline condition.

FIG. 7B shows a representative block diagram for a method 300 corresponding to the discussion regarding FIG. 7A above. In step 302, a waveguide 50 can be positioned in the wellbore 12. A Current set counter (C) and a Baseline set counter (B) can be set to "0". Prior to the environmental condition changing, in step 304, light signals at multiple frequencies can be launched into the waveguide 50, thereby producing a Current Dataset (C) of traces from the respective backscattered signals 56 received from the waveguide 50. This Dataset (C) can be saved as a first Baseline Dataset (B), where $B=C=0$, initially. In step 306, the environmental condition change event can be initiated. It is assumed, for purposes of this discussion, that the change event will be a large change event as described above with regard to FIG. 7A. However, the method 300 also works for change events that are not large enough to require saving off multiple incremental baseline datasets of traces. In step 308, the Current counter (C) is set to $C+1$. In step 310, light signals at multiple frequencies can be launched into the waveguide 50, thereby producing an incremental Current Dataset (C) of traces from the respective backscattered signals 56 received from the waveguide 50. Therefore, for the first execution of step 310, the Current counter (C)=1, and the Baseline counter (B)=0. After the initial execution of step 310 these counters represent the incremental datasets used for the Current Dataset (C) and the Baseline Dataset (B).

In step 312, it is determined whether or not the traces in the Current Dataset (C) and the Baseline Dataset (B) can be correlated. Please note that the correlation of these two datasets can be performed as described in detail in this disclosure. If the traces in the Current Dataset (C) and the Baseline Dataset (B) can be correlated (i.e. YES), then the method 300 proceeds to step 314 where an incremental frequency shift $\Delta v(C,B)$ can be determined and saved off for future calculations. The incremental shift $\Delta(C,B)$ refers to the shift between the Current Dataset (C) and the Baseline

16

Dataset (B), where C and B change per the Current counter (C) and the Baseline counter (B) values. In step 316, it is determined whether or not the environmental condition change event has ended. If YES, then the method 300 proceeds to step 324, where all the incremental frequency shifts $\Delta v(C,B)$ that were saved off in step 314 are combined (i.e. added together) to produce the total frequency shift between the Baseline Dataset (0) and the last Current Dataset (C). From this total frequency shift, the total environmental condition can be determined, and from that the fluid characteristic(s) can be determined, as described in detail in this disclosure.

If the answer in step 316 is NO, then the method 300 returns back to step 308, where C is incremented by 1 (i.e. $C=C+1$), and a new Current Dataset (C) is produced in step 310. Steps 308, 310, 312, 314, and 316 are repeated until the Current Dataset (C) cannot correlate to the Baseline Dataset (B) (i.e. NO in step 312), or the change event has ended (i.e. YES in step 316).

If the answer to step 312 is that the Current Dataset (C) cannot be correlated to the Baseline Dataset (B) (i.e. NO in step 312), then in step 318, it is determined whether or not the Current counter (C) is equal to the Baseline counter (B)+1. If YES, then an error has occurred because the environmental condition changes too fast during the change event. In this case, parameters will need to be adjusted to prevent this error and the method 300 reran. If the answer to step 318 is NO, then, in step 320, the Baseline counter (B) is incremented by "1" (i.e. $B=B+1$), and an incremental Baseline Dataset (B) is set equal to the Current Dataset (C-1) and saved off for future calculations. The method 300 then proceeds to step 312 to verify that the Current Dataset (C) can be correlated to the Baseline Dataset (B). If so, then the steps 314 and 316 can be repeated.

FIG. 8 represents a 3D plot of correlation values generated as a result of comparing a series of initial traces (collected at a first series of SSB frequencies), to a series of final traces (collected at a second series of SSB frequencies). For this example, a series of initial traces were collected for a range of optical signal frequencies from 4.30-4.70 GHz before the environmental condition was changed, and then a series of final traces were collected for a range of optical signal frequencies from 4.30-4.70 GHz after the environmental condition was changed. A correlation value was calculated for each pair of initial and final traces that were compared. A first correlation value was calculated when the initial trace corresponding to the signal frequency of 4.30 GHz was compared to the final trace corresponding to the signal frequency of 4.30 GHz and then the correlation value was plotted in the chart shown in FIG. 8 (lower left point). A next correlation value was calculated when the initial trace corresponding to the signal frequency of 4.30 GHz was compared to the final trace corresponding to the signal frequency of 4.31 GHz and then this correlation value was plotted. This process was continued until all initial traces were individually compared to each one of the final traces and the results plotted in the chart shown in FIG. 8. The key to the right in FIG. 8 defines the shading used to identify the weight of each correlation value in the plot. The lightest color indicates a high correlation value, while the darkest color indicates the lowest correlation value. A line 98 was drawn through the highest correlation values for each trace in the series and indicates that the change in frequency necessary to compensate for the change in the environmental condition was ~40 MHz. This corresponds to a change in the environmental condition, which was temperature in this example, of 30 mK as seen in equation (3) above.

17

The process of comparing the traces, calculating the correlation values, and identifying the best correlation values can be automated to provide expedited results. The following discussion describes various procedures for determining a pair of traces that have the best correlation out of an array of traces. Baseline data refers to traces collected before an event that changes an environmental condition, and subsequent data refers to traces collected after the event. Please note that the subsequent traces can also be collected while the condition is changing. These procedures and their examples focus on temperature as the environmental condition that changes between time period t_1 and time period t_2 . However, other environmental conditions can be determined in a similar fashion. These procedures are only a few of possible procedures for determining the best correlation values between before and after traces.

A First Procedure:

The first procedure can be used for an approach that has baseline data collected at a single frequency, with subsequent data collected over a range of frequencies. This first procedure can be used to compare a baseline trace $A_1(f_{ref}, n)$ to a set of M traces $A_2(f_m, n)$, where the baseline trace $A_1(f_{ref}, n)$, is collected at frequency $f=f_{ref}$, having N elements ($1 \leq n \leq N$), and can be representative of a C-OTDR pattern for the measurement that started at time period $t=t_1$. Please note that, in principle, index n is also representative of time, but at a much smaller scale (e.g. intervals less than 1 ns, typically) compared to measurement time intervals Δt_{meas} of 1 minute or more between the datasets A_1 and A_2 . Also note that baseline trace $A_1(f_{ref}, n)$ can be obtained from the average of several traces, all taken at $f=f_{ref}$ and over a time period from $t=t_1$ to $t=t_1+\Delta t_{meas}$.

The set of M traces $A_2(f_m, n)$, with ($1 \leq m \leq M$), are each N elements long ($1 \leq n \leq N$), and are collected starting at $t=t_2$. Please note that the trace for each frequency f_m can also consist of an average of many traces, collected at the same frequency, so as to reduce the noise for the trace of that frequency. It is assumed that a range of frequencies can be chosen large enough to cover the effect of the largest temperature shift expected (or desired to be measurable) between t_1 and t_2 . This range of frequencies $\{f_m\}$ can be chosen such that the reference frequency f_{ref} is in the middle of the range, but it is not required for the reference frequency f_{ref} to be in the middle of the range.

For this first procedure, a vector of M cross-correlation can be calculated using equation (6):

$$y_{2,m} = Cor_{f_{ref},m} = \frac{1}{N} \sum_{n=1}^N \frac{A_1(f_{ref}, n) - \mu_{A_1,ref}}{\sigma_{A_1,ref}} \times \frac{A_2(f_m, n) - \mu_{A_2,m}}{\sigma_{A_2,m}} \quad (6)$$

with ($1 \leq m \leq M$) and where

$$\mu_{A_1,ref} = \frac{1}{N} \sum_{n=1}^N A_1(f_{ref}, n)$$

is the mean of $A_1(f_{ref}, n)$, and

$$\sigma_{A_1,ref} = \sqrt{\frac{1}{N} \sum_{n=1}^N (A_1(f_{ref}, n) - \mu_{A_1,ref})^2}$$

18

is its standard deviation. Likewise, for the data collected at $t=t_2$, there are M mean values

$$\mu_{A_2,m} = \frac{1}{N} \sum_{n=1}^N A_2(f_m, n),$$

and M standard deviations

$$\sigma_{A_2,m} = \sqrt{\frac{1}{N} \sum_{n=1}^N (A_2(f_m, n) - \mu_{A_2,m})^2}.$$

Unless otherwise stated, the correlation function is calculated using the sum

$$\frac{1}{N} \sum_{n=1}^N \dots$$

which implies that all data points from 1 to N are part of a physical region of interest (i.e. the optical waveguide **50**). If a smaller region of interest is desired, the sum can run only over points which are part of the region of interest.

The set of data points $(f_m, y_{2,m})$ can have a peak centered at frequency $f_{2,peak}$ which can be extracted using a standard peak finding algorithm. A simple way can be to select the frequency f_m that corresponds to the highest value $y_{2,m}$. However, other peak finding algorithms can involve fitting a curve (e.g., a parabola) over the peak portion of the data and taking $f_{2,peak}$ as the location of the peak determined mathematically from the equation of the fitted curve. The offset can be given as $\Delta f_{1 \rightarrow 2} = f_{2,peak} - f_{ref}$. This procedure can be illustrated by the following example for the FIRST PROCEDURE.

An example for the FIRST PROCEDURE:

Optical signals (e.g. laser pulses) can be introduced into the waveguide **50** and a backscattered signal **56** can be measured. During this initial measurement, the SSB modulation frequency can be set to 4.500 GHz. FIG. 9 shows a representative plot of the initial backscattered light signal **56**. Referring to the equations of the first procedure above, this plot can be seen as $A_1(4.500 \text{ GHz}, n)$ where the index "1" indicates the signal **56** has been measured at the first time (11:30 am), 4.500 GHz is the SSB modulation frequency, and $n=1 \dots 15000$ is the number of the individual data points collected. The y-axis of the plot shows an intensity of the signal **56** (in arbitrary units). The x-axis can indicate time, shown here in units of data points. The acquisition rate for this example was 2×10^9 samples/s, therefore each point would correspond to 0.5 nanoseconds. This time scale can indicate a position at which the signal was scattered in the waveguide **50**. The speed of light in a glass fiber can be around $\frac{2}{3}$ of the speed of light in a vacuum, and scattered photons travel twice over the distance to the scattering site (back and forth), which can indicate that each point may correspond to around 5 centimeters. In this example, a region of interest includes the time from data point 7500 to data point 10300, which may correspond to a segment of the optical waveguide **50** that is approximately 140 meter long.

After 5 minutes, multiple backscattered signals **56** were collected at many different SSB modulation frequencies. FIGS. 10A, 10B show two representative signals **56** collected at the same time interval, where $A_2(4.500 \text{ GHz}, n)$ and

19

$A_2(4.520 \text{ GHz}, n)$ represents the two signals **56**, the index 2 indicates that these signals **56** have been measured at the second time period (11:35 am), and the SSB frequency for each signal **56** was $f=4.500 \text{ GHz}$ and $=4.520$, respectively. It should be noted that many signals **56** at many more frequencies than these given here can be collected, but these two are representative of the multiple signals **56** that can be collected in keeping with the principles of this disclosure.

These signals $A_2(f_{SSB}, n)$ are then compared to the initial signal $A_1(4.500 \text{ GHz}, n)$ by calculating the correlation function. Equation (7) calculates the correlation value Corr between the region of interest (data point 7500 to data point 10300) of the initial trace measured at the first time and the region of interest of each of the traces recorded at the second time. Here, μ and σ represent the respective median and standard deviation.

$$\text{Corr}(f_{SSB}) = \frac{1}{10300 - 7500} \sum_{n=7500}^{10300} \frac{A_1(4.500 \text{ GHz}, n) - \mu_{A_1(4.500 \text{ GHz}, n)}}{\sigma_{A_1(4.500 \text{ GHz}, n)}} \times \frac{A_2(f_{SSB}, n) - \mu_{A_2(f_{SSB}, n)}}{\sigma_{A_2(f_{SSB}, n)}} \quad (7)$$

As illustrated by the plot of correlation values vs. SSB frequencies shown in FIG. 11, the one with $f_{SSB}^{best}=4.520 \text{ GHz}$ appears to give the best correlation to the initial trace. Therefore, the temperature change experienced by the optical waveguide during the 5 minutes between the first time period to the second time period can be calculated using equation (2), where the change in frequency is $\sim 20 \text{ MHz}$. Therefore, the change in temperature can be given by

$$\Delta T = \sim 20 \text{ MHz} \times 0.75 \frac{\text{mK}}{\text{MHz}} = \sim 15 \text{ mK}.$$

A Second Procedure:

The second procedure can be used for an approach that has baseline data collected over a range of frequencies, with subsequent data also collected over a range of frequencies. This second procedure can be used to compare a set of P traces $A_1(f_p, n)$, to a set of M traces $A_2(f_m, n)$, where the P traces $A_1(f_p, n)$ are collected at a range of frequencies $f \in \{f_p\}$, having N elements ($1 \leq n \leq N$), and can be representative of C-OTDR patterns for the measurements that started at time period $t=t_1$. Please note that the trace for each frequency f_p can also consist of an average of many traces, to reduce the noise in the trace for each frequency.

As in the first procedure above, the set of M traces $A_2(f_m, n)$, with ($1 \leq m \leq M$), are each N elements long ($1 \leq n \leq N$), and are collected starting at $t=t_2$. Please note that the trace for each frequency f_m can also consist of an average of many traces. Again, it is assumed that a range of frequencies can be chosen large enough to cover the effect of the largest temperature shift expected (or desired to be measurable) between t_1 and t_2 . This range can be chosen such that the reference frequency f_{ref} is in the middle of the range, but it is not required for the reference frequency f_{ref} be in the middle of the range.

For this second method, P vectors of M cross-correlation values can be regarded as a $P \times M$ matrix, and these values can be calculated using equation (8):

20

$$y_{2,p,m} = \text{Corr}_{f_p,m} = \frac{1}{N} \sum_{n=1}^N \frac{A_1(f_p, n) - \mu_{A_{1,p}}}{\sigma_{A_{1,p}}} \times \frac{A_2(f_m, n) - \mu_{A_{2,m}}}{\sigma_{A_{2,m}}} \quad (8)$$

For each p there is a corresponding curve made up of the points $(f_m, y_{2,p,m})$ and a location of the peak for each of these curves, expressed as $f_{2,p,peak}$, can be determined. Thus resulting in a set of P points $(f_p, f_{2,p,peak})$. Those points can describe a line: $f_{2,p,peak} = b f_p + a$. Therefore, the problem can be reduced to a standard linear regression problem with an offset given as $\Delta f_{1 \rightarrow 2} = a$. (Note that the experiment should yield $b=1$ and any deviation from this can be interpreted as due to error in the experiment and can be used as a data quality measure.) With the offset being the difference in frequency between a before trace and an after trace, and with the frequency difference, the change in temperature can be calculated as before.

A Third Procedure:

This third procedure incorporates elements that can make it more robust for automated processing because it incorporates quantitative data quality criteria. The third procedure can be used for an approach that has baseline data collected over a range of M frequencies $\{f_m\}$ and subsequent data collected over the same range of frequencies. This third procedure can be used to compare a first set of M traces $A_1(f_m, n)$ to a second set of M traces $A_2(f_m, n)$, where the first M traces $A_1(f_m, n)$ are collected at a range of frequencies $f \in \{f_m\}$, with ($1 \leq m \leq M$), and having N elements ($1 \leq n \leq N$), which can be representative of C-OTDR patterns for the measurements that started at time period $t=t_1$. Additionally, the second set of M traces $A_2(f_m, n)$ are collected at a range of frequencies $f \in \{f_m\}$, with ($1 \leq m \leq M$), and having N elements ($1 \leq n \leq N$), which are representative of C-OTDR patterns for measurements that started at time period $t=t_2$. Where the first and second set of M traces have a range of frequencies with a span $S = \max(f_m) - \min(f_m)$.

For this third procedure, M vectors of M cross-correlation values can be regarded as an $M \times M$ matrix, and these values can be calculated using equation (9):

$$\text{Corr}_{i,j} = \frac{1}{N} \sum_{n=1}^N \frac{A_1(f_i, n) - \mu_{A_{1,i}}}{\sigma_{A_{1,i}}} \times \frac{A_2(f_j, n) - \mu_{A_{2,j}}}{\sigma_{A_{2,j}}} \quad (9)$$

where

$$(1 \leq i \leq M), \mu_{A_{1,i}} = \frac{1}{N} \sum_{n=1}^N A_1(f_i, n)$$

is the mean of $A_1(f_i, n)$ and

$$\sigma_{A_{1,i}} = \sqrt{\frac{1}{N} \sum_{n=1}^N (A_1(f_i, n) - \mu_{A_{1,i}})^2}$$

is its standard deviation, and likewise for j, $\mu_{A_{2,j}}$ and $\sigma_{A_{2,j}}$. A range of frequency offsets B_k in range $-S \leq B_k \leq S$ can be selected, where S is the frequency span defined above. There can be K such values ($1 \leq k \leq K$), with a uniform spacing of

21

$$\left(\frac{2S}{K-1} \right).$$

A set of K quantities Q_k are calculated using $Q_k = \sum_{m=1}^M \text{Corr}_{k,m}$ where $\text{Corr}_{k,m}$ is obtained via an interpolation process from the $\text{Corr}_{i,j}$ defined above. To understand how this interpolation is done, it should be understood that for each k value, there is a fixed offset B_k , such that, for each value of m, is also associated a frequency $f_k = f_m + B_k$. Depending on the values of f_m and of B_k , f_k may fall inside or outside of the range of frequencies collected. If inside the range, f_k may not fall on one of the values of $\{f_m\}$ in use, then select $f_j \in \{f_m\}$ such that $f_j \leq f_k$ and $f_{j+1} > f_k$, then $\text{Corr}_{k,m}$ is obtained using Equation (10):

$$\text{Corr}_{k,m} = \text{Corr}_{j,m} + \frac{(f_k - f_j)}{(f_{j+1} - f_j)} (\text{Corr}_{j+1,m} - \text{Corr}_{j,m}) \quad (10)$$

If f_k falls outside of the range of frequencies collected, then set $\text{Corr}_{k,m} = 0$. In other words, $\text{Corr}_{k,m} = 0$ if $f_k < \min(f_m)$ or if $f_k > \max(f_m)$.

A normalized quality factor \tilde{Q}_k can be calculated by dividing the quality factor Q_k by the number of correlation values (however, excluding those which were set to zero because $f_k < \min(f_m)$ or $f_k > \max(f_m)$). In other words,

$$\tilde{Q}_k = \frac{Q_k}{\sum_{k=1}^K w(k)}$$

with $w(k) = 1$ for $\min(f_m) < f_k < \max(f_m)$ and $w(k) = 0$ otherwise. A value k can be determined by determining which k value maximizes the quality factor \tilde{Q}_k . Additionally, the frequency shift which maximizes a correlation between before and after traces is given as B_k . From this, the temperature change which occurred between t_1 and t_2 can be expressed as $\Delta T = aB_k$ where the quantity

$$\alpha \approx -0.75 \frac{mK}{\text{MHz}}$$

as stated previously. Operationally, data quality measures can be implemented to verify a validity of the results. For example, the result could be rejected if \tilde{Q}_k is less than a certain threshold (e.g. 0.7), or if $|B_k|$ is above a threshold (e.g. 0.8 S).

From these three procedures, it has been shown how the before and after traces having the best correlation to each other can be identified, even with each set of before and after traces including multiple traces. It should be understood that these are only a few of the procedures that can be used to determine the before and after traces with the best correlation values, and thereby determine a change in an environmental condition in a wellbore, where the environmental condition can be at least one of temperature, pressure, strain, etc.

Thus, a method for detecting environmental changes in a wellbore (or downhole) has been described. Embodiments of the method may generally include positioning (or installing) an optical waveguide 50 along or within a wellbore 12, the optical waveguide 50 being coupled to an optical laser light source 122, 52 that can launch an optical signal 54 into

22

the waveguide 50, and the waveguide 50 being coupled to a receiver 52 that receives a backscattered light signal 56 from the optical waveguide, where the backscattered light signal 56 represents an intensity of backscattered light along a length of the waveguide 50, and thus along a length (or segment) of the wellbore 12. One or more optical signals can be introduced (or launched) into the waveguide 50 at one or more optical signal frequencies and during one or more time periods, thereby resulting in one or more backscattered signals 56 being received by the receiver 52, which produces a trace for each of the one or more backscattered signals 56, where the trace of each backscattered light signal 56 can represent an environmental condition downhole along a length (or segment) of the wellbore.

By causing a change in the environmental condition (e.g. change in temperature, pressure, strain, etc.), additional backscattered light signals 56 can be obtained at one or more frequencies after the environmental condition change has occurred. Comparing the traces generated before the condition change to those generated after the change, can identify a before trace and an after trace that are substantially equal to each other, with the after trace having a difference in frequency from the before trace. This frequency difference can be used to determine the amount of change in the environmental condition that occurred when the environmental change happened.

Other embodiments of the method of detecting a change in an environmental condition in a wellbore may generally include the features given above, as well as generating one or more traces before the condition change event, and generating one or more traces after the change event. The after event traces can be used to compare to the before event traces to identify a before trace and an after trace that are substantially equal to each other, with the after trace having a difference in frequency from the before trace. This frequency difference can be used to determine the amount of change in the environmental condition that occurred when the environmental change event happened. The change in the environmental condition can also be used to identify a location of a production zone 60, 62, 64 in a wellbore 12, when the production zone 60, 62, 64 locations are unknown, which can be the case even in an uncased wellbore 12 without casing string 34 and perforations 36. The method can produce a profile of the environmental condition along the waveguide and therefore, correspondingly identify a location in the wellbore 12 of variations of the environmental condition with respective production zone locations being identified by these variations.

The environmental change event can be opening and/or closing a valve 42, where the valve 42 can be positioned at the surface or at any point within the wellbore 12, such as interconnected in a tubing string 30, deposited in the wellbore 12, positioned in a casing string 34, positioned within tubing string 30, positioned above and/or below production zones 60, 62, 64. The valve 42 can be a one-time use valve with a degradable material, where the valve 42 is initially closed and can be opened by degrading (e.g. melting, dissolving, eroding, etc.) the material to allow fluid flow through the valve. The valve 42 can include swellable material that actuates the valve 42, where swelling of the swellable material can be used to directly restrict fluid flow, or can be used to actuate the valve 42 to selectively permit and prevent fluid flow through the valve 42.

For the foregoing embodiments, the method may include any one of the following steps, alone or in combination with each other:

Determining the amount of change in the environmental condition can include, calculating a difference in frequency between the first and next frequencies, and calculating the change in the environmental condition based on the calculated difference in frequency. Adjusting the optical signal **54** frequency to a next frequency, introducing the optical signal **54** at the next frequency, receiving the next backscattered signal in response to the introduction of the next frequency optical signal, and identifying the differences can be repeated until the first trace substantially equals the next trace. The intensity of the backscattered signal **56** can represent the environmental condition at locations along the wellbore **12**. The environmental condition can be at least one of temperature, pressure, and strain. The first dataset collected prior to the change in the environmental condition can be multiple traces, with the traces being generated in response to multiple different frequencies of the optical signal **54** being launched into the waveguide **50**, and multiple resulting backscattered signals **56** being received by the receiver **52** from the waveguide **50**, where each of the multiple frequencies is different from the other ones of the multiple frequencies. Identifying differences between each one of the first traces to the next trace, and determining the change in the environmental condition when at least one of the first traces is substantially equal to the next trace. The change in the environmental condition can be caused by opening or closing a valve **42** to respectively increase or decrease fluid flow into the wellbore **12** from one or more production zones **60**, **62**, **64**. Determining the amount of change in the environmental condition can include, at least one of a differential fluid pressure, a fluid flow rate, and a fluid composition based on the determined change in the environmental condition. The wellbore can comprise multiple segments, and the first and second traces can represent the environmental condition along a length of at least one of the multiple segments.

Additionally, another embodiment of the method may generally include positioning (or installing) an optical waveguide **50** along (or within) a wellbore **12**, the optical waveguide **50** being coupled to an optical laser light source **122**, **52** that can launch (or introduce) a first optical signal **54** into the waveguide **50** at a first frequency during a first time period **t1**, and the waveguide **50** being coupled to a receiver **52** that receives a first backscattered light signal **56** from the optical waveguide **50** in response to launching the first optical signal **54** in the first time period **t1**, and producing a first trace **90** that represents an intensity of backscattered light along a length of the waveguide **50**, and thus along a length (or segment) of the wellbore **12**. Changing the environmental condition and introducing a second optical signal **54** from the light source **122**, **52** into the optical waveguide **50** at a second frequency during a second time period **t2** while the environmental condition is changing. Receiving a second backscattered signal **56** from the optical waveguide **50** in response to the introduction of the second optical signal **54** and producing a second trace **94**. Comparing the first trace **90** to the second trace **94**, determining that the first and second traces **90**, **94** correlate to each other, and determining a first incremental change in the environmental condition based on differences between the first and second frequencies. Introducing a third optical signal **54** from the light source **122**, **52** into the optical waveguide **50** at a third frequency during a third time period **t3** which is after the environmental change has occurred and the environmental change is stable, receiving a third backscattered signal **56** from the optical waveguide **50** in response to the introduction of the third optical signal **54** and

producing a third trace **96**. Comparing the second trace **94** to the third trace **96**, determining that the second and third traces **94**, **96** correlate to each other, determining a second incremental change in the environmental condition based on differences between the second and third frequencies, and determining the change in the environmental condition by summing the first and second incremental changes.

Additionally, another embodiment of the method may generally include positioning an optical waveguide **50** along the wellbore **12**, introducing first optical signals **54** from a light source **52**, **122** into the optical waveguide **50** at multiple first frequencies during a first time period, receiving first backscattered signals **56** from the optical waveguide **50** in response to the introduction of the first optical signals **54** and producing a set of first traces, making a set of baseline traces equal to the set of the first traces, initiating a change in the environmental condition, introducing second optical signals **54** from the light source **52**, **122** into the optical waveguide **50** at multiple second frequencies after at least a portion of the environmental condition has occurred. Receiving second backscattered signals **56** from the optical waveguide **50** in response to the introduction of the second optical signals **54** and producing a set of second traces, comparing each one of the baseline traces to each one of the second traces, determining that at least one of the baseline traces correlates to at least one of the second traces, determining an incremental change in the environmental condition based on differences between frequencies that are associated with the at least one of the baseline traces and the at least one of the second traces. The method can also include adjusting the multiple second frequencies, to a new set of frequencies to prepare for more sets of traces to be produced, if the environmental change event has not completed (i.e. the environmental condition is still changing).

If the condition is still changing, then the method can repeat 1) the introducing the second optical signals, 2) the receiving the second backscattered signals, 3) the comparing the baseline and the second traces, 4) the determining the correlation, 5) the determining the incremental change and 6) the adjusting the multiple second frequencies until the environmental condition is stable. When the environmental condition is stable, the incremental environmental condition changes can be combined to determine a total environmental change in the wellbore **12**.

For the foregoing embodiments, the method may include any one of the following steps, alone or in combination with each other:

The first, second, and third traces **90**, **94**, **96** can represent an intensity profile of the first, second, and third backscattered signals **54**, respectively, along at least a portion of the wellbore **12**. Determining at least one of fluid type, fluid composition, fluid flow, and fluid pressure differential based on the determined change in the environmental condition. The method can also include determining at least one of the group consisting of fluid type, fluid composition, fluid flow, and fluid pressure differential based on the determined change in the environmental condition, and/or determining multiple incremental changes in the environmental condition during the changing of the environmental condition, and determining the change in the environmental condition by summing the first, second, and multiple incremental changes.

The methods can also include determining that none of the sensing baseline traces correlate with any of the third traces, making the set of sensing baseline traces equal to a last set of the third traces that included at least one of the third traces that did correlate to at least one of the sensing

25

baseline traces, determining at least one of the group consisting of fluid type, fluid composition, fluid flow, and fluid pressure differential based on the total environmental condition change in the wellbore. After the environmental condition change has occurred and the environmental condition is substantially stable, introducing fourth optical signals from the light source into the optical waveguide at multiple fourth frequencies, receiving fourth backscattered signals from the optical waveguide in response to the introduction of the fourth optical signals, producing a set of fourth traces corresponding to the reference portion, comparing each one of the reference baseline traces to each one of the fourth traces, and determining that at least one of the reference baseline traces correlates to at least one of the fourth traces. Calculating a correction value based on a difference between frequencies that are associated with the at least one of the reference baseline traces and the at least one of the fourth traces, and calculating a compensated value for the change in the environmental condition by removing the correction value from the total environmental condition change.

Additionally, a system for detecting a change in an environmental condition has been described. Embodiments of the system may generally include an optical waveguide **50** installed (or introduced) in a wellbore **12**, a light source **122**, **52** that introduces (or launches) an optical laser light signal **54** into the waveguide **50**, and a receiver **52** that can receive a backscattered light signal **56** which represents an intensity of the environmental condition along at least a length (or segment) of the wellbore **12**. The optical laser light signal **54** can be introduced into the waveguide **50** initially at a first frequency during a first time period with the receiver producing a first trace in response to reception of a backscattered light signal **56** from the waveguide **50**. The optical laser light signal **54** can be introduced into the waveguide **50** at a second frequency during a second time period with the receiver producing a second trace in response to reception of a backscattered light signal **56** from the waveguide **50**. The first and second traces are taken at different environmental conditions in the wellbore and the first and second traces are substantially equal to each other. The second frequency is different than the first frequency and the difference between the first and second frequencies can be used to determine the change in the environmental condition that occurred in the wellbore **12**. Other embodiments of the system may generally include the features of the system above, except that at least one of the first and second traces can include multiple traces, and one of each of the multiple first and multiple second traces substantially equal each other. The environmental condition change that can be determined from the difference in frequency between the one of each of the multiple first and multiple second traces can be used to determine the environmental condition change in the wellbore.

For any of the foregoing embodiments, the system may include any one of the following elements, alone or in combination with each other:

The change in the environmental conditions can be due to a valve **42** that is selectively opened and closed, which can variably restrict fluid flow through the wellbore **12**. The valve **42** can be closed (or at least partially closed) for the first time period and opened for the second time period. Alternatively, the valve **42** can be opened for the first time period and closed (or at least partially closed) for the second time period. The environmental condition change can also be caused by other suitable events, as well. At least one of a differential fluid pressure, a fluid flow rate, and a fluid

26

composition of a fluid flowing from a production zone **60**, **62**, **64** into the wellbore **12** can be determined based on the difference between the first and second frequencies. The traces **94**, **96**, **98** are coherent optical time domain reflectometry traces. The wellbore can include multiple segments, and the first and second traces can represent environmental conditions along a length of at least one of the multiple segments. The first frequency can include multiple frequencies, the first trace can include multiple traces, and the first time period can include multiple time periods, with each of the first traces associated with one of the first time periods and one of the first frequencies, wherein one of the first traces can be substantially equal to the second trace, and the change in the environmental condition along the wellbore can be calculated based on the difference between the frequency associated with the one of the first traces and the second frequency.

Additionally, or alternatively, the second frequency can include multiple frequencies, the second trace can include multiple traces, and the second time period can include multiple time periods, with each of the second traces associated with one of the second time periods and one of the second frequencies, wherein one of the second traces can be substantially equal to the one of the first traces, and the change in the environmental condition along the wellbore can be calculated based on the difference between the frequency associated with the one of the first traces and the frequency associated with the one of the second traces.

Additionally, another embodiment of the system may generally include an optical waveguide positioned along the wellbore, a light source that introduces an optical signal into the optical waveguide at a first frequency during a first time period, a receiver that receives a backscattered signal from the optical waveguide in response to the introduction of the optical signal during the first time period, and processing circuitry that can perform operations comprising, producing a first trace which represents an intensity of the backscattered signal along the waveguide, causing a change in the environmental condition, adjusting a frequency of the light source to a next frequency which is different from the first frequency, introducing an optical signal from the light source into the optical waveguide at the next frequency during a next time period, receiving a next backscattered signal from the optical waveguide in response to the introduction of the optical signal during the next time period, producing a next trace which represents an intensity of the next backscattered signal along the waveguide during the next time period, identifying differences between frequencies associated with the first and next traces, and determining the change in the environmental condition based on the differences when the first and next traces are substantially equal to each other.

The operations can also include calculating a difference in frequency between the first and next frequencies, and calculating the change in the environmental condition based on the calculated difference in frequency.

The operations can also include repeating the adjusting, the introducing the optical signal at the next frequency, the receiving the next backscattered signal in response to the introduction of the optical signal at the next frequency, and the identifying the differences until the first trace substantially equals the next trace. The intensity can represent the environmental condition along the wellbore, and the environmental condition can be temperature.

The first frequency can include multiple frequencies and the first trace can include multiple traces with each one of the first traces corresponding to a separate one of the first

27

frequencies, and with each of the first frequencies being different from other ones of the first frequencies. The operations can also include identifying differences between frequencies associated with each one of the first traces and the next trace, and determining the change in the environmental condition based on the differences when at least one of the first traces is substantially equal to the next trace.

The operations can also include opening a valve to increase fluid flow into the wellbore from a production zone, and/or closing a valve to decrease fluid flow into the wellbore from a production zone. The operations can also include calculating at least one of a differential fluid pressure, a fluid flow rate, and a fluid composition based on the determined change in the environmental condition. Along the wellbore can include multiple segments, where the first and next traces represent the environmental condition along a length of at least one of the multiple segments.

Furthermore, the illustrative methods described herein may be implemented by a system comprising processing circuitry that can include a non-transitory computer readable medium comprising instructions which, when executed by at least one processor of the processing circuitry, causes the processor to perform any of the methods described herein.

Although various embodiments have been shown and described, the disclosure is not limited to such embodiments and will be understood to include all modifications and variations as would be apparent to one skilled in the art. Therefore, it should be understood that the disclosure is not intended to be limited to the particular forms disclosed; rather, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the disclosure as defined by the appended claims.

The invention claimed is:

1. A method of detecting changes in an environmental condition along a wellbore, the method comprising:
 positioning an optical waveguide along the wellbore;
 introducing an optical signal from a light source into the optical waveguide at a first frequency during a first time period;
 receiving a backscattered signal from the optical waveguide in response to the introduction of the optical signal during the first time period;
 producing a first trace which represents an intensity of the backscattered signal along the waveguide;
 causing a change in the environmental condition;
 adjusting the first frequency of the light source to a next frequency which is different from the first frequency;
 introducing an optical signal from the light source into the optical waveguide at the next frequency during a next time period;
 receiving a next backscattered signal from the optical waveguide in response to the introduction of the optical signal during the next time period;
 producing a next trace which represents an intensity of the next backscattered signal along the waveguide during the next time period;
 identifying differences between frequencies associated with the first and next traces; and
 determining the change in the environmental condition based on the differences when the first and next traces are substantially equal to each other.

2. The method of claim 1, wherein the determining further comprises, calculating a difference in frequency between the first and next frequencies, and calculating the change in the environmental condition based on the calculated difference in frequency.

28

3. The method of claim 1, wherein the adjusting, the introducing the optical signal at the next frequency, the receiving the next backscattered signal in response to the introduction of the optical signal at the next frequency, and the identifying the differences are repeated until the first trace substantially equals the next trace.

4. The method of claim 1, wherein the intensity represents the environmental condition along the wellbore.

5. The method of claim 4, wherein the environmental condition is temperature.

6. The method of claim 1, wherein the first frequency comprises multiple frequencies and the first trace comprises multiple traces with each one of the first traces corresponding to a separate one of the first frequencies, and with each of the first frequencies being different from other ones of the first frequencies.

7. The method of claim 6, wherein the identifying further comprises identifying differences between frequencies associated with each one of the first traces and the next trace, and wherein the determining further comprises determining the change in the environmental condition based on the differences when at least one of the first traces is substantially equal to the next trace.

8. The method of claim 1, wherein causing the change in the environmental condition further comprises:

opening a valve to increase fluid flow into the wellbore from a production zone; or
 closing a valve to decrease fluid flow into the wellbore from the production zone.

9. The method of claim 1, wherein:

the determining further comprises calculating at least one of a differential fluid pressure, a fluid flow rate, and a fluid composition based on the determined change in the environmental condition; or
 along the wellbore which comprises multiple segments, and wherein the first and next traces represent the environmental condition along a length of at least one of the multiple segments.

10. A system that detects a change in an environmental condition along a wellbore, the system comprising:

an optical waveguide positioned in the wellbore;
 a light source that introduces an optical signal into the waveguide; and

a receiver that receives a backscattered signal from the optical waveguide and produces a trace which represents an intensity of the backscattered signal along the optical waveguide, wherein the intensity represents the environmental condition along the wellbore,

wherein the light source introduces light at a first frequency into the optical waveguide during a first time period and the receiver produces a first trace in response to reception of the backscattered signal from the waveguide,

wherein the light source introduces light at a second frequency into the optical waveguide during a second time period and the receiver produces a second trace in response to reception of the backscattered signal from the optical waveguide,

wherein the second frequency is different from the first frequency,

wherein the first trace is substantially equal to the second trace, and

a change in the environmental condition along the wellbore is calculated based on the difference between the first and second frequencies.

29

11. The system according to claim 10, wherein the change in the environmental conditions is due to a valve that is selectively opened and closed, which variably restricts fluid flow through the wellbore.

12. The system according to claim 11, wherein:
the valve is closed for the first time period and the valve is opened for the second time period; or
the valve is opened for the first time period and the valve is closed for the second time period.

13. The system according to claim 10, wherein at least one of a differential fluid pressure, a fluid flow rate, and a fluid composition of a fluid flowing from a production zone into the wellbore is determined based on the difference between the first and second frequencies.

14. The system according to claim 10, wherein:
the traces are coherent optical time domain reflectometry traces; or
along the wellbore which comprises multiple segments, and wherein the first and second traces represent environmental conditions along a length of at least one of the multiple segments.

15. The system according to claim 10, wherein the first frequency comprises multiple frequencies, the first trace comprises multiple traces, and the first time period comprises multiple time periods, with each of the first traces associated with one of the first time periods and one of the first frequencies, wherein one of the first traces is substantially equal to the second trace, and the change in the environmental condition along the wellbore is calculated based on a difference between the frequency associated with the one of the first traces and the second frequency.

16. The system according to claim 15, wherein the second frequency comprises multiple frequencies, the second trace comprises multiple traces, and the second time period comprises multiple time periods, with each of the second traces associated with one of the second time periods and one of the second frequencies, wherein one of the second traces is substantially equal to the one of the first traces, and the change in the environmental condition along the wellbore is calculated based on a difference between the frequency associated with the one of the first traces and the frequency associated with the one of the second traces.

17. The system according to claim 10, wherein the second frequency comprises multiple frequencies, the second trace comprises multiple traces, and the second time period comprises multiple time periods, with each of the second traces associated with one of the second time periods and one of the second frequencies, wherein one of the second traces is substantially equal to the first trace, and the change in the environmental condition along the wellbore is calculated

30

based on a difference between the frequency associated with the one of the second traces and the first frequency.

18. A method for detecting a change in an environmental condition along a wellbore, the method comprising:

positioning an optical waveguide along the wellbore;
introducing each one of first optical signals from a light source into the optical waveguide at one of multiple first frequencies during a first time period;

receiving first backscattered signals from the optical waveguide in response to the introduction of the first optical signals and producing a set of first traces;
making a set of baseline traces equal to the set of the first traces;

initiating a change in the environmental condition;

introducing each one of second optical signals from the light source into the optical waveguide at one of multiple second frequencies after at least a portion of the environmental condition has occurred;

receiving second backscattered signals from the optical waveguide in response to the introduction of the second optical signals and producing a set of second traces;

comparing the baseline traces to the second traces;

determining that at least one of the baseline traces correlates to at least one of the second traces;

determining an incremental change in the environmental condition based on differences between frequencies that are associated with the at least one of the baseline traces and the at least one of the second traces;

adjusting the multiple second frequencies;

repeating 1) the introducing the second optical signals, 2) the receiving the second backscattered signals, 3) the comparing the baseline traces to the second traces, 4) the determining the correlation, 5) the determining the incremental change and 6) the adjusting the multiple second frequencies until the environmental condition is stable; and

combining the incremental environmental condition changes to determine a total environmental change in the wellbore.

19. The method of claim 18, wherein the determining the correlation further comprises determining that none of the baseline traces correlate with any of the second traces, making the set of baseline traces equal to a last set of the second traces that included at least one of the second traces that did correlate to at least one of the baseline traces.

20. The method of claim 18, further comprising determining at least one of the group consisting of fluid type, fluid composition, fluid flow, and fluid pressure differential based on the total environmental condition change in the wellbore.

* * * * *